

Statewide Marking Guidelines *for Facility Owners*



The JULIE Board of Directors has approved the following Statewide Marking Guidelines to be used by member facility owners.

- Width of each mark should be approximately 2".
- Length of each mark should be approximately 12" - 18".
- Distance between marks depends on site conditions, but no greater than 20 feet.
- Company identification painted at reasonable intervals to allow quick identification.
- End marks should contain arrows if line continues.
- The size of any painted text will not qualify to expand the tolerance zone.

MARKING SAMPLES

LINE

- Any facility less than 12"
- Single facility
- Single conduit

CORRIDOR

- Used when multiple facilities cannot be specifically delineated. Mark should represent located outside edges and number of facilities whenever possible.

OVERSIZED

- Any facility 12" or greater. Mark should represent outside edge of facility.

DUCT PACKAGE

- Mark should represent outside edge whenever possible.

HIGH PRESSURE GAS LINES

- Company should indicate that the line is high pressure gas.

TERMINATION POINT

OFFSETS

- Used when marks cannot be placed directly above buried facility.

NO CONFLICT

**NO/COMED
GAS/OK**

- Recommend company name with the word NO.
- Recommend company name with the word OK.

BURIED SPLICES, VALVES, MANHOLE LIDS

- Circle should represent approximate size of buried facility.

STREET LIGHTS

TRAFFIC CONTROL